





SLR12 Rip Saw, 15HP 3PH 230

Product Images





Description

Whether it's face frames, long runs, or full production, the SLR12 Straight Line Rip Saw has every job covered. Powered by a 15HP main motor, this saw has the capacity for virtually any job. The 12" main blade mounts on a high alloy, heat treated arbor that is precision ground and dynamically balanced for maximum stability and long durability. The caterpillar feed chain blocks are constructed of special grade cast iron that is heat treated and precision machined. The track travels on hardened "V" way guides insuring rigidity and accuracy. A full brush cleaning system with auto-oiler and shut-off gives the conveyor a long service life. All of this is driven by a 2HP feed motor with variable speed to perfectly match the feed rates with your production and finish requirements. A series of seven stock hold downs keep each work piece flat and straight throughout the cutting cycle. Dual anti-kickback devices help prevent discharge of work pieces. The heavy-duty precision rip fence travels on a solid steel guide rail and is micro-adjustable for fast, accurate set up. Controls for rip width, cutting depth, main and feed motors are all mounted up front for fast job changes. The large cast iron table surface supports any size stock and the efficient dust collection port insures a clean work area. From the kiln or cutting glue line, get your production up and running today with the SLR12 from POWERMATIC®.

Additional Information

Stock Number	1791285
Anti-Kickback Devices	2
Arbor Diameter (In.)	1
Blade Diameter (In.)	12
Blade Speed (RPM)	4500
Dust Collection Minimum CFM Required (CFM)	600
Dust Port Outside Diameter (In.)	4
Feed Motor Phase	3
Feed Motor Power (HP)	2
Feed Motor Voltage (V.)	230
Maximum Depth of Cut (In.)	3-7/8
Maximum Ripping Width (In.)	18
Motor Power (HP)	15
Motor Voltage (V.)	230/460
Number of Pressure Rollers	7
Prewired Voltage (V.)	230
Prop 65	Cancer and Reproductive Harm